

Ishida BC-3000 Price-Computing Scale with Printer



PART #	MODEL	CAPACITY
53867Dual Range BC-3000	15 lb/0.005 lb 30 lb x 0.01 lb

The BC-3000 provides unbeatable versatility with its advanced printing and programming capabilities. It is the perfect choice for point-of-sale applications.

The BC-3000's new dual weight range function provides finer weight and tare readings that will save you money over the long haul. Sophisticated data storage is available with 176 speed keys for fast and simple data recall. Providing maximum flexibility in formatting customer labels, its printer output can be configured to use one of seven different font sizes, including reverse printing.

For system integration and automation, the BC-3000 allows basic scale-to-scale communication. This capability enables PLU entries and price changes to be automatically transferred from the master scale to up to four other BC-3000 scales.

Applications

- Sophisticated point-of-sale weighing

Standard Features

- Dual weight range: 0-14.995 x 0.005 lb/15-30 x 0.01 lb
- 88 one-touch preset keys. Each key can be assigned two items using the shift key, for a total of 176 presets
- Thermal dot printer
- Reverse printing
- Seven different character sizes are easily programmed
- Printed data positions can be freely altered, allowing the design of unique labels
- Keyboard formats for presetting and programming can be easily switched using key sheets
- Network up to five BC-3000 scales

Options/Accessories

- 46916.....Produce Platter
- 46917.....Fish Platter
- 71199.....Polyethylene scale shelf, white, 18.25" W x 16" D x 1" H (463mm W x 406mm D x 25.4mm H)
- Consult.....Single weight range firmware
- 46921.....Korean/English language firmware
- Consult.....Chinese/Japanese/English firmware (requires part #47281)
- 46923.....KG version firmware
- 46919.....Remote load cell kit (scale base)
- 47341.....Continuous roll thermal journal paper, 64mm W x 50m L
- 44299.....Additional operating manual
- 48775.....Service manual
- LABEL STOCK**
- 47732.....2.36" x 1.73" (60mm x 44mm)
- 47733.....2.52" x 1.85" (64mm x 47mm)
- 47736.....Pre-printed safe handling instructions on top of label, 2.52" x 2.32" (64mm x 59mm)
- 47745.....Pre-printed safe handling instructions on top of label, 2.52" x 3.34" (64mm x 85mm)

(Specifications on back)

CAPACITY:

0-14.995 x 0.005 lb/15-30 x 0.01 lb

ACCURACY:

1/3000

DISPLAY:

U/P: 6 digits
Weight: 5 digits
Price: 7 digits

PRINTER:

Thermal dot printer

PRINTING SPEED:

70 mm (2.36" per second)

PRESET KEYS:

88 keys (176 presets using shift key)

MEMORY CAPACITY:

128 KB

LABEL SIZE:

2.52" x 3.35" (64mm x 85mm) (variable)
Printing width: Max. 2.36" (60mm)

ELECTRICAL POWER:

115 VAC, 60Hz

POWER CONSUMPTION:

Stand-by: 50W
In operation: 100W

WEIGHT:

26.5 lb (12 kg)

CLASSIFICATION:

NTEP certified, CC# 95-057A3, UL listed

WARRANTY:

One year limited warranty

DIMENSIONS

A: 9.84" (250mm)	G: 17.32" (440mm)
B: 15.75" (400mm)	H: 6.61" (168mm)
C: 2.56" (65mm)	I: 17.72" (450mm)
D: 8.86" (225mm)	J: 7.80" (198mm)
E: 9.45" (240mm)	K: 2.56" (65mm)
F: 4.53" (115mm)	L: 16.54" (420mm)

