



# *IT-8000*

Series Integrated Flat LCD  
Touch Screen Terminals



## **World Class Integrated LCD Touch Screen Terminals**

Now you can obtain extremely robust, fully-featured integrated touch screen terminals at very competitive prices.

- Cast Aluminum Housing
- Great For Harsh Environments
- 12.1" TFT Touch Screen Primary Panel
- Celeron or Pentium III Processor

## SPECIFICATIONS

<b>Processor:</b>	Intel Celeron 850 MHz+ or PIII 500-933 MHz+
<b>Memory:</b>	128 MB RAM Expandable to 512 MB RAM
<b>Video Memory:</b>	Shared Memory up to 64 MB for Primary LCD
<b>Hard Drive:</b>	3.5" Hard Disk Drive
<b>Display LCD:</b>	12.1" TFT LCD Panel
<b>Resolution:</b>	800 x 600
<b>Touch Panel:</b>	ELO 5 Wire Resistive Touch
<b>Serial Port:</b>	2 User Available Com Ports (COM1 & COM2) 2 System Assigned Com Ports (COM3 & COM4) <ul style="list-style-type: none"><li>• COM3 for Primary Touch Screen</li><li>• COM4 for Secondary LCD Touch Screen or VFD Customer Display</li></ul>
<b>Parallel Port:</b>	One Bi-Directional Parallel Port Supports ECP/EEP
<b>USB Port:</b>	Two USB Ports(USB V1.2 Compatible)
<b>Cash Drawer Port:</b>	RJ12 Cash Drawer Port, 12V Actuation Support
<b>Mouse Port:</b>	One PS/2 Mouse Port
<b>Keyboard Port:</b>	One PS/2 Keyboard Port
<b>LAN Port:</b>	10/100Mbps Ethernet Controller, Realtek 8139C
<b>VGA Port:</b>	Standard VGA Port for Second LCD Panel
<b>CD-ROM Port:</b>	Supports SCSI External CD-ROM Drive
<b>Audio Port:</b>	Integrated SIS7018, Sound Blaster Compatible, AC97 Compliant
<b>Secondary Connector Panel:</b>	<ul style="list-style-type: none"><li>• COM4 RJ45 Cable for VFD Customer Display or Second LCD Touch Screen Panel</li><li>• PS/2 Keyboard Port for External Keyboard</li><li>• 4 Pin DIN Connector Supplies Power for the Second LCD Panel</li><li>• VGA Connector for the Second LCD Panel or Second CRT Monitor</li><li>• 36 PIN SCSI II Connector to Attach an External CD-ROM</li></ul>
<b>Power Supply:</b>	AC 100/240 External Adapter Standard
<b>Power Consumption:</b>	40-50W Idle (Standard System & Secondary LCD Panel While Reading HDD)
<b>Operating System:</b>	DOS, Windows 95/98/2000/NT, OS/2, Unix, Netware, Linux
<b>Dimensions:</b>	12.2"W x 9.4"H x 9.8"D
<b>Safety and EMI:</b>	UL, CUL, FCC, CE

## FEATURES

- High Quality Aluminum Diecast, Spill-Resistant Housing
- Internal Full Size HDD
- Secondary Connector Panel and Mounting Bracket for Second Display
- TFT Active Matrix LCD Display
- Integrated Speakers

## OPTIONS

- Integrated VFD/LCD Customer Display
- Integrated Single/Dual/Triple Track MCR
- External USB Floppy Disk Drive
- External SCSI CD-ROM Drive
- Integrated 12" TFT LCD Rear Panel
- 12" ELO 5-Wire Resistive Touch Rear Panel

## APPLICATIONS

- |                            |                   |                    |
|----------------------------|-------------------|--------------------|
| ■ POS                      | ■ Hospitality     | ■ PC/Workstations  |
| ■ Financial/Banking        | ■ Retail Scanning | ■ Hotel Front Desk |
| ■ Medical                  | ■ Kiosks          | ■ Rental Car Desk  |
| ■ Interactive Workstations |                   |                    |



Optional Customer Display



Model 8020 With Optional Secondary Display Panel



Dual 90° Tiltable LCD Displays



Silver Housing